INVESTIGATION OF SORPTION OF CHROMATE ION ON A SYNTHETIC HEMATITE

V. T. BODUNDE^{1*}, F. A. ADEKOLA², and N. ABDUS-SALAM²

¹*Department of Chemistry, Kwara State University, Malete, Nigeria
Email: tovox2001@yahoo.com*

²*Department of Chemistry, University of Ilorin, PMB 1515, Ilorin, Nigeria*

Abstract: A Hematite sample was synthesized using precipitation method and it was characterized using a combination of analytical techniques such as infrared spectroscopy, X-ray diffractometry and atomic absorption spectrometry. The hematite was then studied for its potential to remove chromate ion from aqueous solution. The maximum adsorption capacity was found to be 1.91 mg/g. The influence of contact time, ionic strength and pH on the sorption capacity was also investigated. Maximum adsorption was observed in the range pH 4.0 and pH 6.0 at an optimum time of 3 hours 20 mins. The experimental results were finally analyzed using Langmuir, Freundlich and Temkin isotherms. The Temkin isotherm was found to have the most satisfactory fitting for the sorption data. The sorption kinetics was studied for the pseudo-first order and pseudo-second order models.

Key Words: Heavy metals; Adsorption; point of zero charge; Freundlich; Langmuir and Temkin Isotherms.

INTRODUCTION

Chromium is one of the most widely distributed heavy metals in the earth's crust. It is usually found in two oxidation states i.e., Cr(III) and Cr(VI). Chromium is required in small quantities as an essential trace metal nutrient and its deficiency may result in several physiological disorders. Most of the biological tissues contain Cr(III) which is usually considered to be non-toxic, whereas Cr(VI) is a highly toxic form of the metal to organisms.

Chromium (Cr) pollution is widely of concern throughout the world because of its large magnitude and known adverse health effects (Deng et al. 1995). Dregs of chromium are produced during manufacturing of Cr-containing alloys and salts. These waste materials usually contain a significant amount of chromium (James 1996), which could be leached because of water filtration and/or ground water fluctuation. Chromium contamination of soils and water is also caused by improper disposal of Cr-containing waste-water and sludge produced from corrosion inhibition and electroplating processes.

Chromium exists mainly as hexavalent chromate (Cr(VI)) When released into the environment and trivalent forms (Cr(III)). Chromium species at different oxidation states show substantially different physical and chemical properties. Cr(VI) is an oxidant with high solubility and mobility in soils and aquifers, as well as high toxicity to human and ecosystems; whereas Cr(III) has lower mobility, mostly precipitated as hydroxides or adsorbed onto mineral surfaces. As a result, contamination of Cr(VI) is often controlled by Cr(VI) reduction into Cr(III) using various reducing agents, such as zero-valent

iron (Blowes et al. 1997), iron(II) (Eary et al. 1988a) and organic compounds, (Bartlett et al. 1983).

Reduction of Cr(VI) to Cr(III) is a viable option to remediate sites contaminated with Cr(VI). Fe(II) is a commonly used reductant for Cr(VI) in wastewater treatment. Cr(VI) reduction by Fe(II) is of interest because Fe(II) is found in various types of soil (such as in hematite) and is a primary electron donor in sub-surface environments. Fe(II) can be released from primary silicates and oxides such as muscovite and biotite, and secondary layer silicates such as vermiculite, smectites, dilorites (Eary et al. 1988b) and oxides such as hematite, magnetite and goethite. Cr(VI) reduction by Fe(II) near neutral pH to produce their separate hydroxide solids can be described by the following stoichiometric reaction:

Cr(VI) reduction by Fe(II) has been reported to be very rapid and stoichiometric in solution, (Eary et al. 1988a), (Fendorf et al. 1996). It has also been reported to lead to the formation of mixed iron/chromium solid solution of the form $\text{Fe}_x \text{Cr}_{1-x} (\text{OH})_3$, (Rai et al. 1987).

HEMATITE

Hematite is the mineral form of iron (III) oxides (Fe_2O_3). It is one of several iron oxides. Hematite is a very common mineral, coloured black to steel or silver-grey, brown to reddish brown or red. It is mined as the main ore of iron. Varieties include kidney ore, martite (Pseudomorphs), iron rose and specularite. While the forms of hematite vary, they all have a rust-red streak.

Hematite is harder than pure iron, but much more brittle. Hematite is a part of a complex solid solution oxyhydroxide system having various degrees of water, hydroxyl group, and vacancy substitution that affect the mineral's magnetic and crystal chemical properties (<http://www.mindat.org/min-1856.html>).

SOURCES OF HEMATITE

Huge deposits of hematites are found in banded iron formations. Grey hematite is typically found in places where there has been standing water or mineral hot springs, such as those in Yellowstone. The mineral can precipitate out of water and collect in layers at the bottom of a lake, spring or other standing water. Hematite can also occur without water, however, usually as the result of volcanic activity. Clay-sized hematite crystals can also occur as a secondary mineral formed by weathering processes in soil along with other iron oxides or oxyhydroxides such as goethite (<http://www.mindat.org/min-1856.html>).

SYNTHESIS OF HEMATITE

Hematite can be prepared by a variety of routes. The most recent ones are: solvothermal synthesis, forced hydrolysis, transformation of ferrihydrite in aqueous solution, hydrothermal synthesis and precipitation.

PREPARATION BY FORCED HYDROLYSIS

Forced hydrolysis of acid Fe^{3+} solutions involves hydrolyzing $\text{Fe}(\text{NO}_3)_3$, $\text{Fe}(\text{ClO}_4)_3$ or FeCl_3 solutions at a temperature close to 100°C under strongly acidic conditions (pH 1–2). It is believed that hematite forms under these condition via $\text{Fe}(\text{III})$ hydroxyl polymers which transform through internal rearrangement and dehydration to hematite (Schwertmann et al. 2007).

PREPARATION BY TRANSFORMATION OF FERRIHYDRITE

Hematite production by transformation of ferrihydrite starts with precipitation of ferrihydrite which is then converted to hematite in aqueous suspension by rearrangement and dehydration within ferrihydrite aggregates. This transformation takes place under weakly acid to weakly alkaline conditions. Although ferrihydrite has a low solubility in this pH range, some dissolution may occur leading to goethite precipitation in solution. Such precipitations, therefore, often contain some goethite mixed with the hematite particularly if the pH deviates substantially from neutrality. To avoid goethite, it is essential to conduct all operations at the transformation temperatures ($>70^\circ\text{C}$) or to raise the temperature to

above 100°C in a pressure vessel (Schwertmann et al. 2007).

PREPARATION BY SOLVOTHERMAL PROCESS

Lu et al. (2006) studied the synthesis of hematite by a solvothermal process. 100 ml 1.2 M NaOH solution was dropped into 100 ml 0.6 M $\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$ solution under magnetic stirring at 60°C to form a dark-red transparent $\text{Fe}(\text{OH})_3$ solution. The solution was diluted with water to 250 ml, into which 6.3 g of sodium dodecyl benzene sulfonate was added to produce a yellow precipitate. The precipitate was collected by filtration and dried at 60°C for 24 hr. The dried complex was dissolved into 72 ml dimethyl benzene to form an organic solution and the solution was poured into Teflon-lined autoclaves and heated at 200°C for 6 hr. The product was collected by centrifugation, washed with ethanol and deionized water and dried at ambient temperature.

HYDROTHERMAL SYNTHESIS OF HEMATITE

Wang et al. (2003) prepared well-dispersed $\alpha\text{-Fe}_2\text{O}_3$ nanoparticles by a low-temperature hydrothermal method. Analytical grade iron chloride ($\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$) and cetyltrimethyl ammonium bromide (CTAB, 0.6 g) were dissolved in 40 ml of distilled water. The whole mixture was stirred for 30 min to form a homogeneous solution before it was transferred into a Teflon-lined stainless steel autoclave, sealed and maintained at 80°C of 10 hrs. Finally, it was heated to $150\text{--}180^\circ\text{C}$ for 12 hours with a heating ramping of $1^\circ\text{C}/\text{min}$. after the reaction was completed; the resulting red brown solid product was centrifuged, rinsed with distilled water repeatedly in order to purify the product and finally dried at 100°C under vacuum. The crystalline phase was identified by x-ray diffraction (XRD) and the morphology of the sample was examined by transmission electron microscopy (TEM).

LITERATURE ON SORPTION OF CHROMATE IONS ON HEMATITE THE USE OF HEMATITE FOR CHROMIUM (VI) REMOVAL

The ability of hematite to remove $\text{Cr}(\text{VI})$ from aqueous solutions has been studied at different concentrations, temperatures and pH. The maximum removal (97%) was observed at 40°C and pH 2.7 with initial concentrations of $19.23 \mu\text{mol/L}$ $\text{Cr}(\text{VI})$ and 40 g/L hematite. The equilibrium data obey the Langmuir isotherm for the present system. The reaction dynamics have been studied and the process involves both film and pore diffusion to different extents. Mass transfer and diffusion coefficients have been determined. Thermodynamic parameters indicate the spontaneous and

endothermic nature of the process. The uptake of Cr(VI) increases as pH decreases and the maximum removal has been attributed to the formation of positively charged aquacomplexes of iron at the surface and a subsequent interaction with the dominant HCrO_4^- species. An empirical equation has been developed to predict equilibrium adsorption capacity from knowledge of equilibrium adsorbate concentration (Singh et al. 1993).

Sorption of Cr(VI) onto natural iron and aluminum(oxy)hydroxides: Effects of pH, ionic strength and initial concentration

The performances of removal of hexavalent chromium from aqueous solution were studied using three different oxy-hydroxides: hematite, goethite and α -alumina. Batch experiments were conducted to measure the effects on adsorption of Cr(VI) of different parameters such as pH of the medium, ionic strength, and initial concentration. Results showed that the adsorption of Cr(VI) depends strongly on the pH, but was independent of ionic strength for hematite and goethite. For α -alumina, adsorption is strongly dependent on pH values and ionic strength. Equilibrium studies showed that Cr(VI) had a high affinity in an acidic medium, but decreased as solution pH increased. Equilibrium isotherms were measured experimentally. Results were analyzed by the Langmuir and Freundlich equations using linearized correlation coefficient at room temperature. The characteristic parameters for each isotherm have been determined. The Langmuir equation was found to fit the equilibrium data for Cr(VI) adsorption (Ajouyed et al. 2010).

DFT studies of Cr(VI) complex adsorption on hydroxylated hematite surfaces

The adsorption structures of Cr(VI) species on hydroxylated α - Fe_2O_3 were investigated using density functional theory within a periodic slab model. A broad structural survey of H_2CrO_4 , HCrO_4^- and CrO_4^{2-} adsorbed on different surface sites was carried out. Chromate species adsorb on the hydroxylated surface via an outer-sphere mechanism through H-bonding and ion-dipole attraction. The most stable structure for H_2CrO_4 reveals strong H-bonding to surface and between adsorbates. For HCrO_4^- , a configuration that shows both H-bonding and $\text{Cr}-\text{O}\cdots\text{H}-\text{O}-\text{Fe}$ ion-dipole interaction is the most favored. In the case of CrO_4^{2-} , the most favored adsorption configuration shows the complex standing on the surface with a Cr-O bond aligned on OH, presenting the strongest $\text{Cr}-\text{O}\cdots\text{H}-\text{O}-\text{Fe}$ interaction. In these three species, CrO_4^{2-} displays the strongest interaction with the hydroxylated surface

with no tendency toward reduction observed, in accordance with experiment (Yin et al. 2009).

MATERIALS AND METHOD

All chemicals and reagents used were analytical grade and were used without further purification.

SYNTHESIS OF HEMATITE

Fourty grams of $\text{Fe}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$ was dissolved in 500 ml of doubly distilled water preheated to 90°C and it was precipitated with 300 ml 1 M KOH preheated to 90°C and 50 ml 1 M NaHCO_3 preheated to 90°C was added. The suspension formed was held in a closed polythene flask at 90°C for 48 hrs in an oven (Schwertmann et al. 2007).

CHARACTERIZATION OF HEMATITE SPECIFIC GRAVITY

An empty specific gravity bottle was weighed (W1) and the weighed bottle was filled with water to determine the volume. The bottle was emptied, dried and then filled with hematite sample and reweighed (W2). Specific gravity is given by ratio of difference in masses to the volume of the bottle (<http://www.eformulae.com/chemistry/specific.php>).

$$\text{Specific Gravity} = \frac{W2 - W1}{V}$$

SPECTROSCOPIC AND CRYSTALLOGRAPHIC INFORMATION

Both the pre-sorbed and after-sorbed hematites were subjected to infrared spectroscopic measurement. While, X-ray diffractometry (XRD) was also used to obtain crystallographic information on the hematite sample.

SURFACE-CHEMICAL PROPERTIES DETERMINATION OF POINT OF ZERO CHARGE MASS TITRATION

Various masses of the hematite sample i.e., 0.1, 0.5, 1.0, 1.5 and 2.0 g were suspended in KNO_3 solution of different concentrations (0.1, 0.01, 0.001 M). The initial pH of each sample solution was taken and the solution was allowed to equilibrate for 24 hr and pH was measured. A few drops of 0.01 M HNO_3 solution were added to each solution with the aid of a micropipette to adjust the pH to 7. The sample solution was agitated again with a mechanical shaker for 24 hrs after which the pH was taken and few drops of 0.01 M KOH were added to adjust the pH of the solution to 10. The

Table 1. Physico-chemical properties of synthesized hematite.

Parameters	Results
Colour	Reddish brown
Texture	Fine
Density (g/cm ³)	3.027
% by weight of Fe	63.7%
% by weight of Mn	2.0%
% by weight of Cu	1.5%
% by weight of Zn	1.2%
% by weight of Mg	0.3%
PZC	7.2–10.4
pH	6.26
% yield	91.8

solution was agitated for 24 hrs and pH was re-taken. The values of the different masses of the hematite sample were plotted against pH obtained at different concentrations of KNO₃ solution for each of the stages (i.e., neutral, acidic and alkaline) separately and the point at which the pH became constant with increasing mass gave the point of zero charge (Noh et al. 1989).

ANALYSIS OF CHROMIUM IN AQUEOUS SOLUTION

Chromium was analysed in aqueous solution spectrophotometrically. It involved the determination of the maximum absorption spectrum and standard calibration graph for subsequent measurements.

DETERMINATION OF MAXIMUM WAVELENGTH

The absorption spectrum of chromate solution was determined to select the wavelength of maximum absorbance. The absorbance of the stock solution, i.e., 1,000 mg/l of chromate solution, was taken on a Campec M106 UV-Spectrophotometer at different wavelengths (419–459.5 nm). The absorbances obtained were plotted against the corresponding wavelength. The wavelength (λ_{max}) corresponding to the maximum absorbance was then selected for maximum absorbance measurements. The graph of absorbance versus the wavelength is presented in Fig. 14.

Table 2. Selected Infrared data for synthesized hematite, (Schwertmann et al. 1985).

Peaks	Functional Groups
2,854	O–H Stretch.
722–973	Characteristic band of hematite and O–H deformation.

Table 3. Infrared data for hematite sample after sorption, (Schwertmann et al. 1985).

Peaks	Functional Groups
2,853–2,923	Indicating the presence of hydroxyl stretch
722	Characteristics band of hematite and O–H deformation

CALIBRATION GRAPH OF CHROMATE SOLUTION

The data of absorbance against concentration of the standard solution of chromium was taken. The best straight line is fitted for the data using regression analysis. The graph is illustrated in Fig. 15 with correlation coefficient ($R^2 = 0.9966$).

SORPTION EXPERIMENT

The adsorption experiments were categorized into two types namely:

1. Adsorption Capacity
2. Adsorption Kinetics

DETERMINATION OF ADSORPTION CAPACITY OF HEMATITE FOR CHROMATE SOLUTION

The sorption capacity was determined using varied initial concentration of chromate solution (30–70 ppm) while maintaining the adsorbent (hematite) dosage at 0.5 g per 20 ml of solution. Maximum time of agitation of 24 hrs was used. The mixture of each flask was filtered and the absorbance of the filtrate from each flask was taken. The residual concentration of the filtrate was determined from the calibration curve. The amount sorbed was calculated from the equation (Megat et al. 2007; Horsfall et al. 2005)

FIG. 1. Graph of pH versus mass of sample immediately after equilibration.

FIG. 2. Graph of pH versus volume with 0.1 M KNO₃. FIG. 4. Graph of pH versus volume with 0.001 M KNO₃.

$$q_e = \frac{(C_i - C_f)(\text{mg/l}) \times V(\text{l})}{M(\text{g})}$$

where

- q_e = Amount sorbed at equilibrium (mg/g)
- C_i = Initial Concentration of chromate solution (mg/l)
- C_f = Final Concentration after equilibrium (mg/l)
- V = Volume of chromate solution used (l)
- M = Mass of hematite used (g)

The equilibrium amount sorbed was plotted against initial concentration of solutions to find the equilibrium point where an increase in concentration does not have an effect on the quantity sorbed. The equilibrium concentration was used constantly for sorption kinetics.

DETERMINATION OF ADSORPTION KINETICS

The effects of pH, reaction time and ionic strength were investigated on the sorption capacities of hematite using the following procedures:

Effect of contact time.—The effect of reaction time on sorption capacity was studied by agitating the solution

at different time intervals i.e., 40 min, 80 min, 120 min, 160 min, 200 min and 240 min. The concentration and adsorbent dosage were kept constant i.e., equilibrium concentration as obtained above. Absorbance values were measured and the final concentrations were obtained from the calibration curve. The quantity fixed was then calculated. A graph of quantity fixed was plotted against time.

Effect of ionic strength.—The effect of ionic strength was studied by varying the concentration of KNO₃ (0.001 M, 0.005 M, 0.01 M, 0.05 M and 0.1 M). The concentration, contact time and adsorbent dosage were kept constant, i.e., equilibrium concentration as obtained above. Absorbance values were measured and the final concentrations were obtained from the calibration curve. The quantity fixed was then calculated. A graph of quantity fixed was plotted against ionic strength.

Effect of pH.—The sorption capacity was studied over a pH range of 4 to 9 and the pH was adjusted by addition of 0.01 M HNO₃ or 0.01 M KOH. The concentration, contact time, ionic strength and adsor-

FIG. 3. Graph of pH versus volume with 0.01 M KNO₃.

FIG. 5. Graph of Quantity sorbed versus initial concentration.

FIG. 6. Graph of quantity adsorbed against time.

bent dosage were kept constant i.e., equilibrium concentration as obtained above. Absorbance values were measured and the final concentrations were obtained from the calibration curve. The quantity fixed was then calculated. A graph of quantity fixed was plotted against pH.

RESULTS AND DISCUSSION PHYSICAL PROPERTIES OF HEMATITE

Low percentages of Mn, Cu, Zn and Mg recorded can be accounted for by the presence of these ions as impurities in the reagents used (Table 1)

PERCENTAGE YIELD OF HEMATITE

The percentage yield of the synthesized hematite was calculated to be 91.8% and this is similar to the result earlier obtained by P. Sergey Gubin (2009), using the same precipitation method.

FIG. 7. Graph of quantity adsorbed against ionic strength.

FIG. 8. Graph of quantity adsorbed against pH.

SPECTROSCOPIC STUDIES

Infrared spectra of the hematite sample, which indicates the presence of a characteristic peak of hematite at $722\text{--}973\text{ cm}^{-1}$ (Tables 2 and 3)

The XRD result shows the presence of hematite with rhombohedra shape. In the infrared spectra, peak absorption between $2,853\text{--}2,923$ indicates the presence of hydroxyl stretch and peak absorption at $722\text{--}973$ shows the characteristic band of the hematite and O–H deformation. It was observed from these results that a well formed hematite was synthesized.

DETERMINATION OF POINT OF ZERO CHARGE USING MASS TITRATION METHOD

After equilibration, the point of zero charge was observed to range from 8.5–9.0 for different ionic strengths but after acidic adjustment the point of zero charge dropped to the range 8.03–8.31. However, after

FIG. 9. Langmuir adsorption isotherm plot.

FIG. 10. Freundlich adsorption isotherm plot.

FIG. 11. Temkin adsorption isotherm plot.

alkaline adjustment the point of zero charge increased to the range 8.86–9.03 for different ionic strengths. The values obtained for point of zero charge are in the same range as the one reported by Kosmulski (2004) (Fig. 1).

After titration, the point of zero charge was observed in the range 7.2–10.4 for different ionic strengths (Figs. 2, 3 and 4).

The effects of pH on chromate removal are generally related to the point of zero charge of the adsorbent. Above the point of zero charge value the adsorbent is in a monomeric anionic form and consequently have no affinity for Cr-oxyanions, (Guy et al. 2007), therefore, sorption is expected to be favourable at pH lower than the point of zero charge (i.e., pH < 7.2).

ADSORPTION CAPACITY OF HEMATITE FOR CHROMATE SOLUTION

The amount of hematite and the volume of chromate solution used were the same for all the samples i.e., 0.5 g and 20 ml respectively. The initial concentration was varied between 0 and 70 mg/l. It was observed that as the initial concentration is increased, the concentration increases thereby resulting in an increase in quantity adsorbed after which quantity adsorbed remains constant with increasing initial concentration (Fig. 5). The maximum adsorption capacity has been found to be 1.908 mg/g.

EFFECT OF CONTACT TIME

It is clear that the metal sorption capacity increased with an increase in contact time before attaining equilibrium at 200 min (Fig. 6). The contact time of 200 min was then used for further studies.

INFLUENCE OF IONIC STRENGTH

A steady increase in the amount adsorbed was observed as the ionic strength increases until it gets to

a point where further increase in ionic strength has no effect on the adsorption of chromium (ionic strength >0.01 M) (Fig. 7). The ionic strength of 0.01 M was therefore retained for subsequent experiment.

INFLUENCE OF PH

An adsorption experiment was carried out at pH ranging from 3–9 and a steady increase in quantity adsorbed was observed as pH increases but quantity adsorbed reduces after pH of 6 indicating that chromium adsorption is favorable at a pH value of 6. At this optimum pH, the maximum chromium removal by hematite was found to be 95% and this pH value agreed with the work of El-Chaghaby et al. (2008). At this pH (below PZC), hematite is in cationic form and it has maximum affinity for chromate ions. All subsequent experiments were carried out at pH of 6 (Fig. 8).

LANGMUIR ADSORPTION ISOTHERM

The sorption data were fitted with the Langmuir Adsorption isotherm (Fig. 9). The Langmuir adsorption constants obtained are $q_m = 2.07$ and $b = 0.371$ and the correlation coefficient, $R^2 = 0.927$.

From the observed adsorption efficiency (q_m) value, it can be concluded that the maximum adsorption corresponds to a saturated monolayer of adsorbate on adsorbent in the plane of the adsorbent surface with no transmission of adsorbate in the plane of the adsorbent surface (Krishna et al. 2002; Arivoli et al. 2006). The theoretical value of q_m is in the same range as the experimental value. The observed b (adsorption energy) value shows that the adsorbent prefers to bind acidic ions and that speciation predominates on sorbent characteristics when ion exchange is the predominant mechanism that takes place in the adsorption of chromium ion (Arivoli et al. 2007a). To confirm the

Table 4. Isothermal constants and correlation coefficient.

b	q_m	K_f	n	K_t	b_T	R^2	
Langmuir	0.371	2.07	-	-	-	-	0.9276
Freundlich	-	-	0.8935	0.2321	-	-	0.7373
Temkin	-	-	-	-	1.029	1.682	0.9539

favourability of the adsorption process, the separation factor (R_L) is calculated from:

$$R_L = \frac{1}{1 + bC_o}$$

b = Langmuir constant for adsorption energy

C_o = Initial Concentration

When $R_L > 1$, the adsorption process is unfavourable; $R_L = 1$, it is linear; when $0 < R_L < 1$, adsorption is favourable; and when $R_L = 0$ it is irreversible Weber et al. (1974). The R_L value obtained for the adsorption process under consideration was 0.043 which falls between 0 and 1 and this confirmed that adsorption process is favourable (Arivoli et al. 2007b).

FREUNDLICH ADSORPTION ISOTHERM

After fitting the adsorption data using the Freundlich adsorption isotherm, the Freundlich adsorption constants obtained are $n = 0.2321$, $K_f = 0.8935$ and the correlation coefficient, $R^2 = 0.7373$ (Fig. 10).

Freundlich constants (K_f and n) indicate whether the sorption is favourable or unfavourable, (Renmin et al. 2005). The intercept is an indication of sorption intensity. A relatively slight slope $n < 1$ indicates that the sorption intensity is good over the entire range of concentration studied while a steep slope of $n > 1$ indicate that sorption intensity is good at high concentration but much less at lower concentration, (Mohanty et al. 2006). A high value of K_f is indicative of

high sorption capacity. The low value of K_f (0.8935) observed in this work and the correlation coefficient ($R^2 = 0.7373$) shows that the Freundlich adsorption isotherm does not satisfactorily fit the experimental data.

TEMKIN ADSORPTION ISOTHERM

The Temkin adsorption potential K_T of chromate ion on hematite was 1.029 and the constant b_T , related to the heat of adsorption was $1.682 \text{ KJ mol}^{-1}$ and the correlation coefficient, $R^2 = 0.9539$ (Fig. 11). The low values of the Temkin constants in this study indicate a weak interaction between sorbate and sorbent, (Horsfall et al. 2005), (Adouby et al. 2007). The coefficients of correlation (R^2) indicated that the Langmuir (0.9276) and Temkin (0.9539) isotherms fitted the adsorption data for chromate ion better than the Freundlich (0.7373) isotherm (Table 4).

ADSORPTION KINETICS PSEUDO-FIRST ORDER KINETICS

The pseudo-first order kinetics has been used to analyse the adsorption data to test how it fits with time (Fig. 12).

PSEUDO-SECOND ORDER KINETICS

The pseudo-second order kinetics was also used on the adsorption data of chromium on hematite (Fig. 13).

The coefficient of correlation for the first order rate constant was lower than that of the pseudo-second order model. It was observed that the q_e value from the experiment did not agree with the q_e value obtained

FIG. 12. Graph of $\log (q_e - q_t)$ versus Time (Lagergren plot). FIG. 13. Graph of t/q_t against Time. (Pseudo-second order plot).

Fig. 14. Graph of Absorbance versus Wavelength.

from pseudo-first order plots. This indicates that pseudo-first order kinetics is not sufficient to describe the mechanism of chromate-hematite interactions. The kinetics can therefore be better described by the pseudo-second order kinetic (Table 5)

The plot of t/q_t versus t for pseudo-second order model (Fig. 13) yielded a very good straight line (correlation coefficient, $R^2 = 0.9505$). The pseudo-second order rate constant was 0.312 g mg^{-1} . The theoretical value of q_e also agrees very well with the experimental value. Both facts suggest that the adsorption of chromate ions by hematite follows the pseudo-second order kinetic model (Ye et al. 2008).

CONCLUSION

Hematite has been found to be an effective adsorbent for the removal of chromium from aqueous solution. The adsorption of chromium was found to be dependent on initial concentration of metal ion, pH, ionic strength, and agitation time as expected. The maximum adsorption

Fig. 15. Calibration graph of chromate solution.

Table 5. Kinetic parameters and correlation coefficient.

	q_e (mg/g)	K	R^2
Pseudo-first order	1.18	0.0023 min^{-1}	0.9428
Pseudo-second order	1.908	0.312 (g/mg)	0.9505

capacity obtained was 1.908 mg/g and the maximum removal of chromium was observed at pH 6 with initial concentration of 60 mg/l . The equilibrium adsorption data showed satisfactory fitting with Langmuir and Temkin adsorption isotherms and the adsorption kinetic of the system conforms better to the pseudo-second order kinetics.

LITERATURE CITED

- ADOUBY, K., L. C. KOFFI, W. N. EBOUA, AND B. YAO. 2007. Removal of heavy metal ion (pb^{2+} , Cu^{2+}) in aqueous solutions by pterygota macrocarpa sawdust. *J. Appl. Sci.* 7(14):1864–1872.
- AJOUYED, O., C. HUREL, M. AMMARI, L. B. ALLAL, AND N. MARMIER. 2010. Sorption of Cr(VI) onto natural iron and aluminium (oxy) hydroxides. Effects of pH, ionic strength and initial concentration. *J. Hazardous Materials* 174(1–3):616–622.
- ARIVOLI, S. S., S. JAIN, AND T. RAJACHANDRASEKAR. 2006. Cobalt adsorption on a low cost carbon-kinetics, equilibrium and mechanistic Studies. *Material Sci. Res.* 3:241–250.
- ARIVOLI, S., AND M. HEMA. 2007. Comparative study on the adsorption kinetics and thermodynamics of dyes onto acid activated low cost carbon. *Intern. J. Physical Sci.* 2:10–17.
- ARIVOLI, S., B. R. VENKATRAMAN, T. RAJACHANDRASEKAR, AND M. HEMA. 2007. Adsorption of ferrous ion from aqueous solution by low cost activated carbon obtained from natural plant material. *Res. J. Chem. Environ.* 17:70–78.
- BARTLETT, R. J., AND B. JAMES. 1983. Behaviour of Chromium in soil VI. Interactions between oxidation-reduction and organic complexation. *J. Environ. Sci. Quality* 12:177–181.
- BLOWES, D. W., C. J. PTACER, AND J. L. JAMBOR. 1997. In-situ remediation of chromate contaminated Groundwater using permeable Reactive walls. *J. Environ. Sci. Tech.* 31:3348–3357.
- DENG, B., AND C. KIM. 2007. Kinetic Study of hexavalent Cr(VI) reduction by hydrogen sulfide through goethite surface catalytic reaction. *Geochem. J.* 41:397–405.
- EARY, L. E., AND D. RAI. 1988. Chromate Removal from Aqueous wastes by Reduction with ferrous ion. *J. Environ. Sci. and Tech.* 22:972–977.
- EARY, L. E., AND D. RAI. 1988. Kinetics of chromate Reduction by Ferrous ions, derived from Hematite and Biotite at 25°C . *Amer. Journ. Sci.* 289:180–213.
- EL-CHAGHABY, G. A., N. T. ABDEL-GHANI, AND R. M. EL-NASHAR. 2008. Removal of Cr(III) and Pb(II) from solution by adsorption onto Casuarina Glauca tree leaves. 7(7):3126–3133.
- FENDORF, S. E., AND L. I. G. 1996. Kinetics of Chromate Reduction by Ferrous ions. *Environ. Sci. Tech.* 30(5):1614–1617.
- GUBIN, S. P. 2009. Magnetic nanoparticles, Wiley-VCH Verlag GmPH and Co, Weinheim. 1 Ed. Euro. 14:470.
- GUY, H., D. STUBEN, AND Z. BERNER. 2007. Removal of Arsenic from aqueous solution by natural stellerite and hematite. *Applied Geochem.* 22:1039–1051.
- HORSFALL, M., AND I. S. AYEBAEMI. 2005. Equilibrium sorption study of Al^{3+} , Co^{2+} and Ag^+ in aqueous solutions by fluted pumpkin (Telfaira Occidentalis Hook f) waste Biomass. *Acta.Chem. Slov.* 52:174–181.

- JAMES, B. R. 1996. The challenge of remediating chromium contaminated soil. *J. Environ. Sci. Tech.* 30:248A–251A.
- KOSMULSKI, M. 2004. pH-dependent surface charging and points of zero charge II update. *J. Colloid and Interface Sci.* (275):214–224.
- KRISHNA, D. G., AND G. BHATTACHARY. 2002. Adsorption of methylene blue on Kaolinite. *Applied Clay Sci.* 20:295.
- LU, J., C. DIARONG, AND J. XIULING. 2006. Fabrication, Characterization and Formation Mechanism of Hollow Spindle-like Hematite via Solvothermal Process. *J. Colloid Interface Sci.* 303(2):437–443.
- MEGAT HANAFIAH, M. A. K., W. S. WAN, H. ZAKARIA, AND S. C. IBRAHIM. 2007. Batch study of Liquid-Phase Adsorption of lead ions using Lalang (*Imperata cylindrical*) leaf powder. *J. Bio. Sci.* 7(2):222–230.
- MOHANTY, K., M. JHA, B. C. MEIKAP, AND M. N. BISWAS. 2006. Biosorption of Cr (VI) from aqueous solutions by *Eichhornia Crassipes*. *J. Chem. Engin.* 11:71–77.
- NOH, J. S., AND J. A. SCHWARZ. 1989. *J. Colloid Interface Sci.* 130:157.
- RAI, D., B. M. SASS, AND D. A. MOORE. 1987. Chromium (III) Hydrolysis constants and solubility of Chromium (III) Hydroxide. *Inorganic Chemistry* 26:345–349.
- RENMIN, G., S. YINGZHI, C. JIAN, L. HUIJUN, AND Y. CHAO. 2005. Effect of chemical modification on dye adsorption capacity of peanut hull. *Dyes and pigments* 67:17a.
- SCHWERTMANN, U., P. CAMBER, AND E. MURAD. 1985. Properties of Goethite of varying crystallinity. *Clay and Clay Min.* 33:369–378.
- SCHWERTMANN, U., AND R. M. CORNELL. 2007. *Iron Oxides in the laboratory, Preparation and characterization*. Wiley-VCH Verlag GmbH, Weinheim, Germany doi:10.1002/9783527613229.fmatter.
- SINGH, D. B., G. S. GUPTA, AND D. C. RUPAINWAR. 1993. The use of hematite from chromium(VI) removal. Pollution Research Laboratory, Department of Applied chemistry, Institute of Technology, Banaras Hindu University Varanasi-221 005, India. *J. Environ.Sci.Health A28(8)*:1813–1826.
- WANG, X., C. XIANGYING, M. XUCHU, AND Z. HUANGUI. 2003. Low-Temperature Synthesis of α Fe_2O_3 Nanoparticle with a Closed Cage Structure. *Chem. Phys. Lett.* 384(4–6):391–393.
- WEBER, T. W., AND R. K. CHAKRABORTI. 1974. Pore and solid diffusion models for fixed bed adsorbers. *J. Amer. Inst. of Chem. Engin.* 20:228.
- YE, L., W. YU-HUA, AND H. CHUA-BING. 2008. Removal of anionic ions from single material solution by bauxite tailings modified with $\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$. *J. Cent. South Univ. Tech.* 15:656–662.
- YIN, S., AND D. E. ELLIS. 2009. DFT studies of Cr(VI) complex adsorption on hydroxylated hematite (1102) surfaces. *Surface Sci.* 603(4):736–746 <http://www.eformulae.com/chemistry/specific.php>. <http://www.mindat.org/min-1856.html>